



Specification **IEC 60034-1**
 Manufacturer **AmTecs**
 Motor type **AM1-IE3 80G2**
 Rated power **1.1 kW S1 Duty**
 Speed **2880 rpm**
 Voltage **220V / 400V**
 Frequency **50 Hz**
 Connection **Delta / Star**
 Full load current **4 A / 2.31 A**
 No-load current
 Enclosure **IP55**
 Insulation class **F (temp. rise B)**
 Max. ambient temp **40 °C**
 Max. altitude **1000 mtr above sea level**
 Comment
 Cable entry **M20 x 1.5**
 Construction **Cast Iron**
 Weight **21 Kg**
 Type number
 Warranty

Efficiency class **IE3**
 Load data **100%**
 Efficiency **82.7 %**
 Power factor **0.83**
 Sound pressure level (1m) **58 dB(A)**
 Resistance R20 (open)
 Resistance R20 (Delta)
 Full load torque **3.65 Nm**
 Starting / Full load torque **2.6**
 Pull up / Full load torque
 Pull out / Full load torque **3.5**
 Starting / Full load current (DOL) **7.5**
 Starting / Full load current (Y/D)
 Rotor Inertia
 Bearing DE **6204**
 Bearing NDE **6204**

AmTecs Ltd	
Charnham Park, Hungerford Berkshire, RG17 0YT	
Tel: +44 (0) 1488 686970	sales@amtecs.co.uk
Fax: +44 (0) 1488 686968	www.amtecs.co.uk